

TUFO ROMANO PORCELAIN TILE



## TUFO ROMANO PORCELAIN TILE



13" x 13" TUFO ROMANO VANILLA PORCELAIN TILE  
46-097



3" x 8" TUFO ROMANO VANILLA BULLNOSE  
52-198



8" x 10" TUFO ROMANO VANILLA WALL TILE  
52-103



13" x 13" TUFO ROMANO BIANCO PORCELAIN TILE  
46-098



3" x 8" TUFO ROMANO BIANCO BULLNOSE  
52-199



8" x 10" TUFO ROMANO BIANCO WALL TILE  
52-107

## TUFO ROMANO PORCELAIN TILE



13" x 13" TUFO ROMANO NOCE PORCELAIN TILE  
46-099



3" x 8" TUFO ROMANO NOCE BULLNOSE  
52-200



8" x 10" TUFO ROMANO NOCE WALL TILE  
52-111

### PACKAGING INFORMATION

DESCRIPTION	ITEM CODE			LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	VANILLA	BIANCO	NOCE					
13" x 13" TUFO ROMANO PORCELAIN TILE	46-097	46-098	46-099	44.22	11	12.91	58	748.90
8" x 10" TUFO ROMANO WALL TILE	52-103	52-107	52-111	26.62	20	10.76	92	989.92
3" x 8" TUFO ROMANO BULLNOSE	52-198	52-199	52-200	12.87	30	N/A	105	3150 pcs.

### GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	13" x 13"
THICKNESS		mm – in	7.6 mm – 5/16"
WATER ABSORPTION	EN ISO 10545-3	( % )	≤ 0.5
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	4
SCRATCH HARDNESS		(Mohs)	9
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 300
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.60
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.90
DCOF (WET)	ANSI B101.3		≥ 0.70
SHADE VARIATION			V1