

RAGNO  USA

ARTE COLOR BODY PORCELAIN TILE | RECTIFIED | MADE IN THE USA



live inspired





live inspired

ARTE

COLOR BODY PORCELAIN TILE | RECTIFIED | MADE IN THE USA



AJ3P Arte BI
20"x20" Rectified
AJ3L Arte BI
13"x13" Rectified
AJ3S Arte BI
12"x24" Rectified
AJ3V Arte BI
3^{1/4}"x6^{1/2}" Rectified

AJ3Y Arte BI
Brick Mosaic
13"x13"

AJ3N Arte BG
20"x20" Rectified
AJ3K Arte BG
13"x13" Rectified
AJ3R Arte BG
12"x24" Rectified
AJ3U Arte BG
3^{1/4}"x6^{1/2}" Rectified

AJ3X Arte BG
Brick Mosaic
13"x13"

AJ3Q Arte MA
20"x20" Rectified
AJ3M Arte MA
13"x13" Rectified
AJ3T Arte MA
12"x24" Rectified
AJ3W Arte MA
3^{1/4}"x6^{1/2}" Rectified

AJ3Z Arte MA
Brick Mosaic
13"x13"

- Floor Tile
- Wall Tile
- Rectified Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- V3 Moderate Variation
- Frost Resistant
- Meets ADA Recommendations
- IV Abrasion Resistance
- 0.6 C.O.F. (Wet)
- 0.7 C.O.F. (Dry)
- VOC Certified No VOC
- 21% Minimum Pre-Consumer Recycled Content

TRIMS



AJ33 Arte BI Bullnose
AJ32 Arte BG Bullnose
AJ34 Arte MA Bullnose
3"x13"

TECHNICAL SPECIFICATIONS				
DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD	
Water Absorption	≤ 0.50%	≤ 0.50%	C373	
Frost Resistance	As Reported	Resistant	C1026	
Scratch Resistance	MOHS 1-10	6	MOHS SCALE	
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 605 lbf.	C648
	13"x13"	≥ 250 lbf.	≥ 407 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499	
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499	
Wedging (Squareness)	+/- 0.25 % or +/- 0.8 mm*	Within Standard	C502	
Warpage (Flatness)	+/- 0.40 % or +/- 1.8 mm*	Within Standard	C485	
Abrasion Resistance	Class 0 - Class V	Class IV	C1027	
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028	
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028	
Chemical Resistance	Class A - Class E	Class A	C650	
Stain Resistance	Class A - Class E	Class A	C1378	

* Whichever is less



Contributes to LEED Credits

