

Medallions & Borders by Florida Brick & Clay

It's been said that accessories make the outfit. Like a string of pearls add style to a black dress, Medallions & Borders by FBC add pizzazz and dimension to a paver installation.

Medallions by FBC blend old traditions of art with architectural design to create visual excitement. The Sunshine Pavers Medallion is three feet square in size and adds an artistic focal point to entryways, patios, porches, driveways, pool decks, and plazas. Each is individually handmade by craftsmen who take great pride in their work.

FBC offers the option to custom make medallions to complement your decorating scheme. Any color offered in the Sunshine Pavers line may be selected to fit within the medallion patterns. Ask our Customer Service Representatives for more details.



W-400's with a Sunshine Pavers Medallion and Rubble Border.



Custom made medallion using the colors W-100, W-200, W-300 and W-620.



Custom medallion using the colors W-100, W-800, and W-620.



Sunshine Pavers®

Installation and Maintenance Guidelines

A complete guide for specification and installation of Sunshine Pavers for architects and designers is available by request from Florida Brick & Clay Co., Inc. General guidelines call for setting in mortar beds or thin-set installations with grouted joints (3/8" min.). Any questions as to quality or shading should be brought to the attention of the distributor or manufacturer before installation. Installation of product constitutes acceptance, unless there are latent defects that occur after installation. Expansion joints are recommended according to the TCNA specifications. For best results, manufacturer recommends using a sealer before grouting and also selecting a grout color similar in color to the pavers. All grout haze should be removed after grouting using a sponge or towel and clean water. Acid cleaners should be used according to manufacturer's instructions. Due to its harsh nature, manufacturer does not recommend using muriatic acid to clean grout and pavers. After pavers are clean of all grout haze, Florida Brick & Clay Co., Inc. recommends sealing the pavers and grout with a penetrating sealer, such as NATURAL CLAY PRODUCTS PENETRATING SEALER to act as a water barrier. When pavers are exposed to oil or grease FBC recommends using an oleophobic penetrating sealer.

Outdoor installations such as sidewalks, patios and pool decks can be routinely cleaned by spraying pavers down with a water hose and sweeping. Deeper cleaning may require using a high pressure washer. Indoor installations require sweeping or vacuuming loose dirt prior to mopping using a neutral detergent cleaner such as, Hillyards Super Shine All.



Use Natural Clay Products Penetrating Sealer before grouting.

FBC is a member of the following ceramic trade organizations:



Florida Brick & Clay Co. Inc.
 1708 Turkey Creek Road
 Plant City, FL 33566
 Phone: 813-754-1521
 Fax: 813-754-5469
www.floridabrickandclay.com
 email: customerservice@floridabrickandclay.com

SUNSHINE PAVER PRODUCTS

SUNSHINE PAVERS are unglazed, 1/2" thick, wire-cut textured clay pavers. They are fired to a semi-vitreous body making them very durable, easy to clean and will not fade with age. Sunshine Pavers provide a perfect surface treatment to exterior walkways, porches, patios, pool decks, driveways, plazas, commercial lobbies, restaurant entryways and industrial floors.



W-300 Sunset

ANTIQUÉ PAVERS have a rustic, antique character created using a blend of crème and black coatings on a red flashed base. Like antique bricks, small defects which add to the character of the pavers, such as chipped corners, small cracks, color & sizing deviations are considered a characteristic of this product. Best results are achieved by blending several boxes during installation.



W-1100 Colonial Blend

FLASHED PAVERS have an irregular smoked edge around the perimeter of the paver giving a rugged elegance. The flashing is created during the firing process and the amount of flash varies with each unit. The flash penetrates into the surface and will not fade over time. Blending the pavers throughout installation produces the best results.



W-450 Wine Red Flash

TEAKWOOD PAVERS are made to simulate the variations in graining found in teakwood. There are two colors to choose from. One has a beige base with brown veining and the other has a sienna base with brown veining. Each paver is unique in the amount of graining that it has, similar to the variations that occur in nature. Blending during installation produces best results.



W-500 Sunset Marble

INDUSTRIAL PAVERS Sunshine Pavers are produced in a 1" thickness when special heavy duty use requires additional strength to stand up to the abuse of industrial applications with truck and forklift traffic. The wire-cut surface provides extra traction for footing when the surface is wet from cleanup. The pavers are kiln fired and have a high compressive strength.



W-400 Wine Red 1" Thick

COLOR SELECTIONS


SPECIALTY COLORS
EARTH TONE COLORS
HIGHLIGHT COLORS



W-450 WINE RED FLASH



W-1100 COLONIAL BLEND



*W-500 SUNSET MARBLE



*W-700 DESERT MARBLE



W-200 DESERT SAND



W-300 SUNSET



W-400 WINE RED



W-900 MOCHA BLEND



W-100 KEYSTONE




W-620 CORAL




W-800 PEWTER

STANDARD SIZE



3 5/8" x 7 5/8" x 1/2"
9.2cm x 19.4cm x 1.3cm

TRIM SHAPES



Bullnose 4" edge Bullnose 8" edge

Shade Variations in Pavers

Variations of shade or color is one of the natural artistic qualities inherent in all fired clay products. All samples are submitted only as a representation of the product. *W-500 and W-700 should not be used for outdoor applications in freeze thaw conditions.

Pattern Designs



W-400 Wine Red



Antiqué Pavers

PERFORMANCE SPECIFICATIONS		
TEST	ASTM	Sunshine Pavers
Coefficient of Friction	C1028-89	Dry: 1.08
		Wet: 1.03
Compressive Strength	C902-79	19,190 psi
Freeze/Thaw	C67-78 C902-79	no weight loss or disintegration
Water Absorption	C902-79	4.8%
Warpage	C902-79	avg. 1.0 mm
Saturation Coefficient	C902-79	.80
Abrasion Resistance	C902-79	Type I
		0.025
Efflorescence	C902-79	none
Breaking Strength	C648-71	352 lbs. avg.



W-900 Mocha Blend with W-300 Sunset as Accent Strip. Meets ADA Guidelines



W-800 Pewter



W-620 Coral bordered with W-800 Pewter and W-100 Keystone